



VERSION	CHANGE CONTENT	DATE
V00	FIRST ISSUE	2007-04-20
V01	修改模組特性	2007-07-20

TYPE	A	B
LED B/L	13.5	8.9



DETAIL DOTS
SCALE: 5:1

PIN	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
NAME	VSS	VDD	V0	RS	R/W	E	DB0	DB1	DB2	DB3	DB4	DB5	DB6	DB7	LED+	LED-

SPECIFICATIONS

1. DISPLAY TYPE: STN/TRANSLECTIVE/POSITIVE-Y-G
2. LCD DRIVING VOLTAGE: 4.7V
3. LOGIC VOLTAGE: 5.0V
4. VIEWING DIRECTION: 6.0° CLOCK
5. OPERATING TEMP: -10° C-60° C
6. STORAGE TEMP: -20° C-70° C
7. DRIVE MODE: 1/16 DUTY, 1/5 BIAS
8. BACKLIGHT: YELLOW GREEN/BOTTOM BACKLIGHT/5.0V
9. CONTROL/DRIVE IC: SPLC780D-001B-C/SPLC063A1-C
10. OTHER:

NOTE:

VIEWING



DESCRIPTION:

C/D

SCALE: FIT
SHEET: 1 OF 1
TINSHARP ELECTRONICS CO.,LTD.

UNIT:	PROJECTION	MODEL	SERIAL NUMBER
mm		TC1604A-01	MLX0076
APP:		CHK:	DWN:
DATE:		DATE:	

